ASK Proxima C1 Compact (Ultralight LX1) Projector
Technical and Functional Specifications

Display Technology	• 0.9 in. Polysilicon LCD x 3 with micro lens array
Resolution	• XGA (1024 x 768)
Resolution Supported	• VGA (640 x 480)
	• SVGA (800 x 600)
	• XGA (1024 x 768)
	• SXGA (1280 x 1024)
	• MAC (640 x 480 - 1280 x 1024)
Number of Colors	• 16.7 million colors
Brightness	• 800 ANSI lumens
Contrast Ratio	• 300:1 (full-on, full-off)
Computer Compatibility	• IBM PC or compatibles
	• Apple Macintosh
Video Compatibility	• NTSC 3.58, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, MESECAM
Input Sources	• 1 computer, 1 video, 1 S-video, 2 audio
H-Sync Range	• 15-100 kHz
V-Sync Range	• 43-130 Hz
Bandwidth	• 140 MHz
Aspect Ratio	• 4:3
Image Size (Diagonal)	• 1.8 ft. to 20.8 ft. (0.5 m to 6.3 m)
Projection Lens	• Manual zoom and focus 1.3:1 ratio
	• Focal length: 38 mm to 55 mm, f/1.8-2.1
Projection Distance	• 3.6 ft. to 33 ft. (1.1 m to 10 m)
Keystone Correction	• 10
Projection Method	• front/rear, desktop/ceiling
Lamp (Life)	• 120 watt UHP (4,000 hours)
Audio	• 2 x 1 w stereo
Remote Control	• Batmouse III with mouse control, laser pointer, and projector control
Dimensions	• 9.3 in. W x 13.6 in. L x 3.9 in. H
	• 23.6 cm W x 34.7 cm L x 9.9 cm H
Weight	• 8.1 lbs. (3.7 kg)
Power Consumption	• 200 watts
Power Requirements	• 100V - 240V AT 50/60 Hz (+/- 10%)
Operating Temperature (Sea Level)	• 41 - 95F (5 - 35C)
On-Screen Languages	• English, Japanese, German, French, Italian, Spanish
Audible Noise	• 38db
Approvals	• FCC Class A, UL, C-UL, CE
Warranty	• Two years on parts and labor (excluding lamp)